

20ft ISO Container



Uniteam has an extensive experience in design, supply and rental of ISO Containers. We offer these types of products in different sizes and designs, according to customer requirements and international standards.

20ft ISO container is suitable for storage and as a basis for other special units: Insulated Containers, Workshop Containers, First Aid Containers and many more.

Uniteam ISO containers are standardized steel units used for many different purposes. Units are used within a global containerized intermodal freight transport system, are CSC approved and tested according to ISO 1496-1.

Specification

	WEIGHT (kg)			EXTERNAL DIMENSIONS (mm)			INTERNAL DIMENSIONS (mm)		
	TARE	PAYLOAD	MGW	LENGTH	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT
20ft ISO Container	2250	28230	30480	6050	2440	2590	5900	2350	2390

SHIPMENT - SPECIAL HANDLING:

- Will not fit on standard liftgate.
- Must be removed from shipping carrier with a forklift or other suitable lifting device.

DIMENSIONS:

- Adjustable Legs (Actual): 27 7/8 - 35 3/8"
- Shelf Clearance: 20 1/4"
- Clearance Between Legs: 90"
- Holes to Bolt Table to Floor: 3/8" diameter

MATERIAL:

- Tabletop:
 - Top/Bottom: 1/2" Industrial grade particle board
 - Core: MDF (Medium Density Fiberboard)
 - Lacquer finish

FEATURES:

- Tabletop Edges:
 - Front/Back: Rounded
 - Sides: Square

CAPACITY:

- Capacity based on evenly distributed weight, reduced if loaded in center.
- Capacity reduced to 450 lbs if using casters.

THICKNESS:

- Legs:
 - Primary Material: 12 gauge
 - Upper Section: 13 gauge

USAGE:

- Bottom shelf is not adjustable.

Availability: [In Stock](#)

Unit Weight: 203 lbs.

Last ordered 1 on
06/04/2020

[Instructions](#)

[Catalog Page 501](#)

[Email Item](#)

Country of Origin: USA

DIMENSIONS:

- Shelf (Usable): 35 1/2 x 16"
- Inside: 36 x 17 1/4 x 67"

THICKNESS:

- Shelves & Bottom: 20 gauge
- Top, Header & Sill: 22 gauge
- Doors, Sides & Back: 24 gauge

MATERIAL:

- Powder coated
- Not fireproof

TEMPERATURE:

- 20° - 150° F

FEATURES:

- 3-point locking system.
- Includes 2 keys.
- Shelves:
 - Adjust in 2" increments.
 - Four adjustable
 - Minimum space from highest shelf position to top of cabinet: 15"

CAPACITY:

- Total Unit: 850 lbs

Ships Via Motor Freight

Availability: **In Stock**

Unit Weight: 113 lbs.

Last ordered 2 on
06/04/2020

[Instructions](#)

[Parts List](#)

[Catalog Page 489](#)

[Email Item](#)

Country of Origin: USA

[Additional Info](#)

[Parts](#)

[Shopping Lists](#)

[Request a Catalog](#)

DIMENSIONS:

- Outside:
 - Width: Add 4 3/4" to listed dimensions.
 - Depth: Add 1 1/4" to listed dimensions.
- Beam Height: 3"
- Footplate Mounting Holes: 9/16" diameter

CAPACITY:

- Shelf capacity listed in the chart is based on evenly distributed loads.
- Overall: Not to exceed 17,000 lbs with maximum distance between shelves 24"

USAGE:

- For hand-loading only. (Not for use with forklifts.)
- Each shelf can hold 12 shelf supports.
- Racks are for non-seismic applications.

Availability: [In Stock](#)
Unit Weight: 207 lbs.

[Instructions](#)

[Catalog Page 465](#)

[Email Item](#)

Country of Origin: USA